

- New series in modern design
- Extreme durability thanks to low wear wheel and disc drive

#### Technical specifications:

##### Housing:

ABS/PC, high impact, black

##### Cap:

Polycarbonate, transparent, high impact

##### Fixing:

Base, bracket or tube mounting

##### Terminal:

Screw

##### Drive:

Wheel and disc drive, motor in gravity centre

##### Installation position:

as required

##### Halogen lamp:

GY 6.35 35 W 12V/24 V

##### Mirror rotation speed:

180 r.p.m.

##### Service life of drive:

> 3.000 h

##### Duty cycle:

100 %

##### Bulb included in assembly

- High protection rating IP 65
- High impact resistance 20 Joules
- Can be mounted as required

#### Order specifications:

Order No.	Voltage (V)	Rated current
883 □ 00 54	12 V =	3 A
883 □ 00 75	24 V ≅	1,6 A
883 □ 00 77	115 V ≅	0,35 A
883 □ 00 68	230 V ~	0,17 A



1 = red

2 = green

3 = yellow

4 = clear

5 = blue

Please state colour code.

#### Special parts:

975 883 01	Bracket for wall mounting
975 883 02	Flange for tube mounting
975 845 10	Tube, 25 mm ø, 100 mm long
975 845 25	Tube, 25 mm ø, 250 mm long
975 840 91	Metal base for tube 25 mm ø

#### Spare parts:

955 883 34	Halogen lamp 35 W for 12 V = 115 V ≅, 230 V ~
955 883 35	Halogen lamp 35 W for 24 V ≅

