



SYS 1308-W2E

Plug type: [USA](#), [Europe](#), [UK](#)

Input Voltage Type: Universal Range

AC Input Voltage: 90~264 Vac

AC Input Frequency: 47~63 Hz

AC Input Current: 1A RMS

No. of Outputs: Single O/P

Load Regulation: +/-5%

Min. O/P Amper: 0A

Operation Temperature: 0~40 C

Protection: Short, Over Voltage, Over Current

MTBF: 35 000 Hours

Hold Up Time: 10 ms

Safety: GS/TUV, CB

Weight: 143 grams

Dimension: 75 mm (L), 34 mm (W), 43 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional Safety
SYS1308-0303-W2E	3	3	1.00	
SYS1308-0312-W2E	3	12	0.25	
SYS1308-0315-W2E	3	15	0.20	
SYS1308-0503-W2E	5	3	1.66	
SYS1308-0505-W2E	5	5	1.00	
SYS1308-0508-W2E	5	7.5	0.66	
SYS1308-0509-W2E	5	9	0.55	

SYS1308-0605-W2E	6	5	1.20
SYS1308-0606-W2E	6	6	1.00
SYS1308-0608-W2E	6	7.5	0.80
SYS1308-0609-W2E	6	9	0.66
SYS1308-0612-W2E	6	12	0.50
SYS1308-0615-W2E	6	15	0.40
SYS1308-0805-W2E	8	5	1.60
SYS1308-0806-W2E	8	6	1.33
SYS1308-0808-W2E	8	8	1.00
SYS1308-0815-W2E	8	15	0.53
SYS1308-0903-W2E	9	3	3.00
SYS1308-0906-W2E	9	6	1.50
SYS1308-0908-W2E	9	7.5	1.20
SYS1308-0909-W2E	9	9	1.00
SYS1308-0918-W2E	9	18	0.50
SYS1308-1005-W2E	10	5	2.00
SYS1308-1012-W2E	10	12	0.83
SYS1308-1015-W2E	10	15	0.66
SYS1308-1206-W2E	12	6	2.00
SYS1308-1209-W2E	12	9	1.33
SYS1308-1212-W2E	12	12	1.00
SYS1308-1224-W2E	12	24	0.50
SYS1308-1305-W2E	13	5	2.60
SYS1308-1505-W2E	15	05	3.00

SYS1308-1506-W2E	15	06	2.50
SYS1308-1508-W2E	15	7.5	2.00
SYS1308-1509-W2E	15	9	1.66
SYS1308-1512-W2E	15	12	1.25
SYS1308-1515-W2E	15	15	1.00
SYS1308-1518-W2E	15	18	0.83
SYS1308-1808-W2E	18	08	2.25
SYS1308-1809-W2E	18	09	2.00
SYS1308-1812-W2E	18	12	1.50
SYS1308-1815-W2E	18	15	1.20
SYS1308-1818-W2E	18	18	1.00
SYS1308-1824-W2E	18	24	0.75
SYS1308-2412-W2E	24	12	2.00
SYS1308-2415-W2E	24	15	1.60
SYS1308-2418-W2E	24	18	1.33
SYS1308-2424-W2E	24	24	1.00



Product Code Rule

