


LISOVACÍ KABELOVÁ OKA

DIN 46235

materiál: E - Cu trubka

povrch: galvanicky pocínováno, případně mechanicky leštěno



2

jmenovitý průřez mm ²	svorník Ø	objednávací číslo*	iden. číslo	rozměr mm								nářadí	 100 ks ~ kg	 balení ks
				d ₁	a	b	d ₂	d ₄	c ₁	c ₂	l			
6	M 5	101 R/5	5	3,8	10	8,5	5,3	5,5	6,5	7,5	24	tabulka strana 2.15 - 2.16	0,240	100
	M 6	101 R/6				8,5	6,4		7,5	8			0,300	
	M 8**	101 R/8				13	8,4		10	10			0,340	
10	M 5	102 R/5	6	4,5	10	9	5,3	6	7	8,5	27		0,370	100
	M 6	102 R/6				9	6,4		7,5	8,5			0,360	
	M 8**	102 R/8				13	8,4		10	10			0,380	
16	M 6	103 R/6	8	5,5	20	13	6,4	8,5	7,5	8	36		1,190	100
	M 8	103 R/8				13	8,4		10	10			1,220	
	M 10	103 R/10				17	10,5		12	12			1,300	
	M 12**	103 R/12				18	13		13	13			1,270	
25	M 6	104 R/6	10	7	20	14	6,4	10	7,5	8	38		1,510	50
	M 8	104 R/8				16	8,4		10	10			1,540	
	M 10	104 R/10				17	10,5		12	12			1,620	
	M 12	104 R/12				19	13		13	13			1,660	
35	M 6**	105 R/6	12	8,2	20	17	6,4	12,5	7,5	8	42		2,770	50
	M 8	105 R/8				17	8,4		10	10			2,850	
	M 10	105 R/10				19	10,5		12	12			2,840	
	M 12	105 R/12				21	13		13	13			2,790	
	M 14**	105 R/14				21	15		14,5	14,5			2,700	
50	M 8	106 R/8	14	10	28	20	8,4	14,5	10	10	52		4,460	50
	M 10	106 R/10				22	10,5		12	12			4,480	
	M 12	106 R/12				24	13		13	13			4,400	
	M 14**	106 R/14				24	15		14,5	14,5			4,300	
	M 16	106 R/16				28	17		16	16			4,570	
70	M 8	107 R/8	16	11,5	28	24	8,4	16,5	10	10	55		5,920	50
	M 10	107 R/10				24	10,5		12	12			6,020	
	M 12	107 R/12				24	13		13	13			5,890	
	M 14**	107 R/14				24	15		14,5	14,5			5,800	
	M 16	107 R/16				30	17		16	16			6,130	

* objednávací číslo pro provedení bez povrchové úpravy (nepocínované) s dodatkem „bk“


** nenormalizováno

LISOVACÍ KABELOVÁ OKA

DIN 46235

materiál: E - Cu trubka

povrch: galvanicky pocínováno, případně mechanicky leštěno



jmenovitý průřez mm ²	svorník Ø	objednávací číslo*	iden. číslo	rozměr mm								nářadí	 100 ks ~ kg	 balení ks
				d ₁	a	b	d ₂	d ₄	c ₁	c ₂	l			
95	M 8**	108 R/8	18	13,5	35	28	8,4	19	12	12	65	tabulka strana 2.15 - 2.16	9,210	25
	M 10	108 R/10				28	10,5		12	12			8,970	50
	M 12	108 R/12				28	13		13	13			8,620	50
	M 14**	108 R/14				28	15		14,5	14,5			8,780	25
	M 16	108 R/16				32	17		16	16			9,000	50
120	M 10	109 R/10	20	15,5	35	32	10,5	21	15	16	70		11,400	50
	M 12	109 R/12				32	13		16	17			11,310	50
	M 14**	109 R/14				32	15		18	19			11,450	25
	M 16	109 R/16				32	17		19	20			11,240	50
	M 20	109 R/20				38	21		21	22			11,030	25
150	M 10	110 R/10	22	17	35	34	10,5	23,5	15	16	78		16,380	10
	M 12	110 R/12				34	13		16	17			16,290	25
	M 14**	110 R/14				34	15		19	20			16,380	10
	M 16	110 R/16				34	17		19	20			16,170	10
	M 20	110 R/20				40	21		21	22			15,900	10
185	M 10	111 R/10	25	19	40	37	10,5	25,5	15	16	82		18,960	10
	M 12	111 R/12				37	13		16	17			18,110	10
	M 14**	111 R/14				37	15		19	20			19,210	10
	M 16	111 R/16				37	17		19	20			18,740	25
	M 20	111 R/20				40	21		21	22			18,690	10
240	M 12	112 R/12	28	21,5	40	42	13	29	16	17	92		27,000	10
	M 14**	112 R/14				42	15		19	20			27,580	10
	M 16	112 R/16				42	17		19	20			27,370	25
	M 20	112 R/20				45	21		21	22			26,880	10
300	M 14**	113 R/14	32	24,5	50	46	15	32	19	22	100		33,290	5
	M 16	113 R/16				46	17		19	22			32,940	
	M 20	113 R/20				46	21		22	22			33,240	
400	M 14**	114 R/14	38	27,5	70	54	15	38,5	25	25	115		69,380	5
	M 16	114 R/16				54	17		25	25			68,540	
	M 20	114 R/20				54	21		25	25			65,400	
500	M 16**	115 R/16	42	31	70	60	17	42	25	25	125		83,310	1
	M 20	115 R/20				60	21		25	25			81,580	
625	M 16**	116 R/16	44	34,5	80	64	17	44	25	25	135		79,600	1
	M 20	116 R/20				64	21		25	25			79,690	
800	M 16**	117 R/16	52	40	100	75	17	52	30	30	165		150,000	1
	M 20	117 R/20				75	21		30	30			149,000	
1000	M 16**	118 R/16	58	44	100	83	17	58	30	30	165		199,000	1
	M 20	118 R/20				83	21		30	30			195,000	



* objednávací číslo pro provedení bez povrchové úpravy (nepocínované) s dodatkem „bk“

** nenormalizováno